

# SHIELDâ Compacting Felts

## Construction

- **Endless** - No Seams or Splices to create mark-off or negatively affect the felts tensile strength.
- **Exceptionally Smooth Surface as a result of the fibers and needling techniques used.**
- **Superior Strength and Durability due to the base fabric construction.**
- **Heat-Set** for excellent dimensional stability and ease of tracking.
- **Batt-on-Base Construction** - Consists of a woven scrim (base) with a needled surface (batt).

## Composition

UNITED STATES SUPPLY offers several styles of Compacting/Steaming Blankets depending upon the application. For example, we recommend our COMPAC 3000® for steam applications, while our COMPAC 7000® is typically used for high heat processes.

Other styles are available, however, so please advise us of the manufacturers name of the machine and the typical process performed when ordering, so we may better service your needs.

## Sizes

- **LENGTH** - 2 to 25 mtrs. (6.56 - 82').
- **WIDTH** - 51 mm to 3810 mm. (2 - 150").
- **THICKNESS** - 10 mm to 25 mm. (0.11 - 1").

## Notes:

- Since some Compacting Felts must be as thick as possible to achieve the maximum shrinkage of the fabric, we manufacture felts up to 25 mm thick.
- The dimensions listed above are standard. We do, however, manufacture outside these standard dimensions per request.

## Standard Machines

Compacting Felts from UNITED STATES SUPPLY are suitable for use on Ferraro, Heliot, Monti, Muzzi, Poong Kwang, Santex, Sperotto Rimar, Weiss and other machines.

# UNITED STATES SUPPLY

INTERNATIONAL SUPPLIERS to PRINTING and TEXTILE FINISHING

TEL: (704) 399-4276 FAX: (704) 393-5628 [www.ussupplyinc.com](http://www.ussupplyinc.com)

P.O. Box 668945 Charlotte, NC 28266-8945

